

300	PROCESS OF DYNAMIC SEALING	334	..Particular wall structure
301	.Close proximity seal (e.g., contactless, fluent, etc.)	335	.Axially facing packing cup
302	..Magnetic	336	.For below ground apparatus
303	..Labyrinth	337	..Longitudinally actuated packer
304	..Formed by pressurized sealing fluid introduced to form barrier	338	...Packing sleeve
305	..Floating ring or bushing	339Expanded by wedging member
306	..Relatively rotatable radially extending sealing face member (e.g., face, mechanical, etc.)	340Particular wall structure
307	..Formed by flexible projection	341Reinforcing feature
308	.Contained or compressed by gland member in packing box	342	...Plural stacked rings
309	.Peripheral radially sealing flexible projection (e.g., lip, piston cup seal, etc.)	343	.Seal (e.g., wiper, oil saver, stripper, etc.) accommodates irregular size of inner part
310	.Piston ring for internal combustion engine	344	.Segmented radially actuated packer (e.g., oil saver, gas saver, etc.) for above ground apparatus
311	.Flexible ring	345	SEAL BETWEEN RELATIVELY MOVABLE PARTS (I.E., DYNAMIC SEAL)
312	PROCESS OF STATIC SEALING	346	.Diverse and distinct dynamic seals
313	.Between parts of internal combustion engine	347	..Close proximity seal (e.g., contactless, fluent, etc.)
314	.Pipe, conduit, or cable	348	...And relatively rotatable radially extending contacting sealing members (e.g., face, mechanical, etc.)
315	.Using flexible sleeve, boot, or diaphragm	349And circumferential peripheral radially sealing flexible projection (e.g., lip seal, etc.)
316	.Forming in place (i.e., in situ)	350	...And circumferential contact seal
317	SEAL COMBINED WITH INDICATOR, SAMPLER, OR INSPECTION FEATURE	351Peripheral radially sealing flexible projection (e.g., lip seal, etc.)
318	.Fluid pressure	352	..Relatively rotatable radially extending contacting sealing members (e.g., face, mechanical, etc.)
319	.Fluid temperature	353	..And circumferential peripheral radially sealing flexible projection (e.g., lip seal, etc.)
320	.Fluid leakage	354	.Helically threaded part
321	.Wear, proper seating, or presence	355	.Brush seal
322	SEAL FOR WELL APPARATUS	356	.For journal box (e.g., railway car journal, etc.)
323	.Installation, removal, assembly, disassembly, or repair feature	357	.For rotary piston
324	.For overpressure control device (e.g., seal for a blowout preventer, etc.)	358	.Relatively rotatable radially extending sealing face member (e.g., face, mechanical, etc.)
325	..Segmented radially actuated (e.g., ram type, etc.)	359	..Temperature responsive feature
326	..Rotatable	360	...Accommodates or prevents thermal distortion
327	..Axially compressed ring		
328	..Longitudinally actuated packer for above ground apparatus		
329	..Contained or compressed by gland member in packing box		
330	...For line or cable		
331	.Inflatable packer		
332	..Deforms radially inward		
333	..And inflating medium control		

361	..Multiple sealing faces (e.g., double seals, etc.)	392Between sealing face member and shaft or part relating to shaft
362	...Floating intermediate sealing face member	393Particular connecting feature to sealing face member
363Including an outwardly axial biasing member	394	...Peripheral radially sealing flexible projection (e.g., lip seal, etc.)
364	...Concentric and radially spaced	395U- or V-shaped cross-sectional profile
365	...Three or more	396	...Axially compressed packing
366	...Shaft mounted sealing face members biased axially away from each other	397	...Frictionally engaged or interfitting projection and recess
367	...Shaft mounted sealing face members biased axially towards each other	398	..Eccentric, gyratory, or oscillatory motion
368	...Housing mounted sealing face members biased axially away from each other	399	..Particular sealing face member configuration
369	...Housing mounted sealing face members biased axially towards each other	400	...Hydrodynamic feature
370	..Installation, removal, assembly, disassembly, or repair feature	401	...Fluid passage to the sealing face
371	...Unitized seal assembly (e.g., cartridge, etc.)	402	...Flexible projection (e.g., lip seal, etc.)
372Having rotation prevention (i.e., antirotation) feature for the sealing face member	403	...Angled or tapered sealing face
373Lug or rib	404	..Made of particular material
374Retains opposed sealing face members	405	...Ceramic
375Mounted in housing or casing	406	...Metal
376Snap fit into groove	407	...Elastomeric or plastic
377	..Particular axial biasing feature	408	..Introduction, circulation, or removal of fluid
378	...Magnetic	409	.Close proximity seal (e.g., contactless, fluent, etc.)
379	...Particular spring feature	410	..Magnetic
380Made of elastomeric material	411	..Gap or clearance
381Frustoconical shape	412	...Labyrinth
382O-ring shape	413Having adjustable member
383Imbedded in another material	414Formed by cellular pockets (e.g., honeycomb, etc.)
384Washerlike shape	415Having wear resistant, abradable, or ablative member
385Arrangement or location	416Segmented
386Radially biasing member creates axial bias	417Formed by multiple washers
387	...Fluid pressure	418Formed by plural grooves or projections on opposing surfaces
388Creates counter pressure	419Interfitting or overlapping
389And bellows or diaphragm	420And axially oriented
390	..Particular secondary mounting seal or driving connection	421	...Having installation, removal, assembly, disassembly, or repair feature
391	...Flexible sleeve, boot, or diaphragm	422	...Floating ring or bushing
		423	..Impeller (e.g., slinger, etc.)

424	...Rib or groove on radial extending surface	455	...Arcuate wall
425	...And static sealing means affected by rotational movement	456	...Coating, treatment, or wall insert
426Actuated by counterweight	457	...Having passageway for fluid return, pressure relief, or venting
427	...Forms centrifugal liquid barrier	458	..Piston ring having single piece noncircular or multiturn (e.g., helical, spiral, oblong, elliptical, polygonal, etc.) shape
428Having cup or chamber inside the impeller or another rotating member	459	..Piston ring including exposed port, slot, pocket, groove, channel, recess, or bevel
429	...Fluid collector or receiver	460	...Circumferential groove, channel, recess, or bevel
430	...Helical groove or thread on axially extending surface	461Axially spaced
431	..Formed by pressurized sealing fluid introduced to form barrier	462Ports
432	...External device or system	463Ports
433	.Centrifugal force affects change in displacement, shape, or contact	464	...Circumferentially spaced ports
434	.Piston ring or piston ring expander or seat therefor	465	...Circumferentially spaced slots, pockets, grooves, channels, recesses, or bevels
435	..Having installation, removal assembly, disassembly, or repair feature	466	..Piston ring displays twisting or torsion
436	..Piston ring having peripheral radially sealing flexible projection (e.g., piston cup, etc.)	467	..Particular piston ring expander
437	...Having particular mounting, retaining, or supporting feature	468	...Separate and other than metal
438	...Having C, U, or V cross- sectional profile	469	...Bias limiting feature
439Axially facing cup	470	...Adjustable loading feature
440	..Piston ring surface of dissimilar material or hardness	471	...Thermal expansion feature
441	...Insert	472	...Annular expander nested in annular groove of the piston ring
442	...Surface coating, plating, or impregnation	473Between piston rings
443Nitrided	474And contacting surfaces therebetween are complementary
444Chromium	475Having more than one pair of such surfaces
445	..Rotation limiting feature (i.e., antirotation)	476Inclined or beveled groove contacting expander having dissimilar contour
446	...Between rings	477	..Slotted or undulating circular band including inclined or axially facing seat for the piston ring
447	..Floating piston ring	478Axially spaced axially facing seats
448	..Material other than metal	479Circular band having radially displaced undulations
449	..Particular piston seat	480Circular band having axially displaced undulations
450	...Helical form	481U-shaped circular band radially directed either inwardly or outwardly throughout its circumference
451	...Stepped walls		
452	...Oblique wall		
453More than one oblique wall		
454Having parallel walls		

482	...Circumferentially spaced separately seated radially acting bias feature	511	...Having installation, removal, assembly, disassembly, or repair feature
483Disposed in socket or about pin	512	...Fluid introducer or director
484	...Radially extending tongue formed from expander	513External device or system
485	...Undulating periphery providing axially extending face against inner perimeter of the piston ring	514Drain, pressure relief, or vent
486	...Bias feature adjoining opposed ends of split or segmented piston ring	515Passage through axial facing surface
487	...Segmented	516Spacer between seals (e.g., lantern ring, etc.)
488	...For axially adjacent piston rings	517Between packing boxes
489	..Sectional piston ring structure	518	...Plural distinct packing boxes
490	...Eccentric or variable thickness component ring	519	...Segmented packing boxes
491	...C, L, T, U, V, or Z cross- sectional profile	520	...Particular gland feature
492Three or more sections	521Segmented
493	..Segmented piston ring	522Spring bias
494	..Separate bridging piece for gap in piston ring	523Disposed about external bolt or stud
495	...Secured to end	524Eye or T-type bolt
496	..Split single piece piston ring having opposed asymmetrical mirrored ends	525Internally threaded
497	...Arcuate or beveled mating surfaces	526Externally threaded
498	..Split single piece piston ring having other than opposed asymmetrical mirrored ends	527	...Wear sleeve
499	...Arcuate or beveled mating surfaces	528	...Helically coiled packing
500	..Circumferential contact seal for other than piston	529	...Having particular cross- sectional seal profile
501	..And magnetic bias	530C-, M-, U-, V-, X-, or Z- shaped
502	..For valve stem in internal combustion engine	531Wedging surface
503	..Accommodates gyratory or oscillatory motion	532Made of elastomer or plastic
504	...Flexible connection between seal and another part	533Segmented
505	...Oscillates perpendicularly to axis of motion	534	...Particular seal material or construction
506	...Arcuate bearing surface	535Composite
507Partially spherical	536Fibrous component
508	...Axially spring biased	537Braided, woven, or twisted
509Coaxial spring	538Distinct sheath or covering
510	..Contained or compressed by gland member in packing box	539Graphite
		540Elastomer or plastic
		541Metal
		542	...Consisting of loose-fill type packing
		543	..Segmented ring
		544	...Having pressure balancing or radial bias reduction feature
		545	...Radial biasing spring element other than nominal garter spring
		546	...Particular segment end structure
		547Interfitting projection and recess
		548	...Plural complementary interfitting rings

549	..Peripheral radially sealing flexible projection (e.g., lip seal, etc.)	578	..Having circumferentially adjustable biasing element
550	...Made of metal or is a scraper	579	..Having floating ring or bushing (i.e., circumferentially contacting)
551	...Having installation, removal, assembly, disassembly, or repair feature	580	...Radially translatable in groove
552	...Having pressure relief or venting feature	581And biased
553	...Bias feature other than nominal garter spring	582	...Made of elastomer or plastic
554Embedded spring	583	...Inflatable seal or seal biased by inflatable member
555Radially extending finger spring	584	..Extrusion preventing (i.e., antiextrusion) structure
556Material other than metal	585	..Elongated sleeve or bushing
557Axially extending helical or spiral spring	586	..Seated in groove having stepped walls
558Particular fluid pressure responsive bias	587	..Seated in groove having oblique wall
559	..Hydrodynamic sealing feature	589	..Radially backed by resilient or elastomeric member
560	...Dimensional aspect of the flexible projection (e.g., angle, length, radius, thickness, etc.)	590	SEAL BETWEEN FIXED PARTS OR STATIC CONTACT AGAINST RELATIVELY MOVABLE PARTS
561	...Intermediate flexible bending portion	591	.Contact seal between parts of internal combustion engine
562	...Plural peripheral radially sealing flexible projections	592	..Particular coating or layer of sealing material
563Having interposed fluid receiver or director	593	..Having compression limiting feature
564Having insert between the flexible projections	594	..Particular dimensions or configuration of sealing bead or formation
565On radial facing side of single seal	595	...Metallic
566Both radial sides of the single seal (e.g., X-shaped, Y-shaped, etc.)	596	...Elastomeric
567Radially facing U or V cross-sectional profile	597	..Heat dissipating, cooling, or insulating feature
568Including an excluder or wiper	598	..Having installation, removal, assembly, disassembly, or repair feature
569	...Lining or insert	599	..Having flow restrictor
570	...Made entirely of fluorocarbon material	600	..Covering member or eyelet for opening
571	...Wear sleeve	601	...Covering fire ring or sealing formation
572	...Particular mounting, frame, casing, or reinforcement feature	602	.Contact seal for a pipe, conduit, or cable
573Peripheral mounting static seal	603	..Plural interfitting seal members for installation on the individual joined pipes, conduits, or cables
574Protrusion or bead cross-sectional profile	604	..Allows rolling or folding
575Secured by molding or bonding	605	..Hollow, fluid-filled, or inflatable
576Secured by clamping	606	..And wall
577By distinct members	607	..Sleeve type

608	..Inserted between end-to-end pipe, conduit, or cable joint	640	...Anchoring feature extending through seal
609	...Having installation, removal, assembly, disassembly, or repair feature	641	...Groove structure on the seal or part
610	...Spirally wound structure	642Channel-shaped
611	...Extrusion preventing (i.e., antiextrusion) or compression limiting feature	643Single seat formed by plural recesses
612	...Having plural projections	644	..Particular cross-sectional seal profile
613	...Hose coupling	645	...Hollow or filled chamber
614	...Each end has recess for the seal	646Inflatable
615	..Having axially spaced projections	647	...C-, U-, or V-shaped
616	..Having associated mounting or retaining feature	648	...Plural projections along sealing surface
617	...Molded or cast into the pipe, conduit, or cable	649Plural projections along opposite sealing surfaces
618	...Axially related or embedded coil spring	650	..Particular sealing material or construction
619	...Axially related backing ring	651	...Embedded reinforcement
620Clamping gland	652	...Distinct sheath or covering
621Particular axially acting feature	653Metal
622Threaded gland	654	...Plural layers
623Particular gland shape		
624And seal secure together		
625	...Particular and located on the pipe, conduit, or cable		
626	..Particular seal shape		
627	..Particular seal material or construction		
628	.Contact seal for other than internal combustion engine, or pipe, conduit, or cable		
629	..Magnetic		
630	..Having installation, removal, assembly, disassembly, or repair feature		
631	..Split including end joining structure		
632	..Segmented periphery		
633	..Spirally wound structure		
634	..Flexible sleeve, boot, or diaphragm		
635	...Dome-, cup-, or bell-shaped, or for ball joint		
636	...Tubular or frustoconical shape having corrugated wall portion		
637	..Having particular associated mounting or retaining feature		
638	...Extrusion preventing (i.e., antiextrusion) structure		
639	...Compression limiting feature		

CROSS-REFERENCE ART COLLECTIONS

902	SEAL FOR STERLING ENGINE
903	SEAL FOR ROTATING KILN OR DRUM
904	VISCOUS SEAL
905	T-SHAPED OR I-SHAPED RING MEMBER INCLUDING SEAL ON A SIDE
906	SEAL FOR ARTICLE OF INDEFINITE LENGTH (E.G., STRIP, SHEET, ETC.)
907	PASSAGEWAY IN ROD OR SHAFT
908	SEAL FOR USE IN ROTATING AND RECIPROCATING ARRANGEMENT
909	SIMILAR SEALING STRUCTURES FOR MOUNTING ON PISTON AND ABOUT ROD
910	O-RING SEAL
911	SEAL COMBINED WITH NOMINAL MOTION TRANSMITTING DEVICE
912	.Spline connection
913	SEAL FOR FLUID PRESSURE BELOW ATMOSPHERIC (E.G., VACUUM, ETC.)
914	BACKUP SEAL FOR FAILURE OF PRIMARY SEAL
915	SEAL INCLUDING COMPRESSION SET FEATURE
916	SEAL INCLUDING VIBRATION DAMPENING FEATURE

917	SEAL INCLUDING FRANGIBLE FEATURE	FOR 100	RADIALLY CONTAINED PACKING WITH
918	SEAL COMBINED WITH FILTER OR FLUID SEPARATOR		AXIALLY ACTING FOLLOWER (277/ 102)
919	SEAL INCLUDING ELECTRICAL FEATURE	FOR 101	.Piston (277/103)
920	SEAL INCLUDING ELECTROMAGNETIC SHIELDING FEATURE	FOR 102	.Sectional follower (277/104)
921	CLOSURE OR WEATHER STRIP SEAL	FOR 103	.Bolted flange (277/105)
922	BONDING OR JOINING FOR MANUFACTURE OF SEAL	FOR 104	..Spring biased flange (277/106)
923	.Shrink-fitting for the assembly of seal	FOR 105	.With operating handle (277/107)
924	DEFORMATION, MATERIAL REMOVAL, OR MOLDING FOR MANUFACTURE OF SEAL	FOR 106	.With tool engaging means (277/ 108)
925	SNAP FIT FEATURE FOR MOUNTING OR ASSEMBLY OF SEAL	FOR 107	.Weight actuated (277/109)
926	SEAL INCLUDING FLUID PRESSURE EQUALIZING OR BALANCING FEATURE	FOR 108	.Screw thimble (277/110)
927	SEAL INCLUDING FLUID PRESSURE DIFFERENTIAL FEATURE	FOR 109	..With locking means (277/111)
928	SEAL INCLUDING PRESSURE RELIEF OR VENT FEATURE	FOR 110	.Screw (277/112)
929	SEAL FEATURE WHERE CHANGE IN OPERATION OR CONDITION INDUCES ADDITIONAL LEAKAGE CONTROL	FOR 111	.With operating mechanism (277/ 113)
930	SEAL INCLUDING HEATING OR COOLING FEATURE	FOR 112	.Unidirectional movement (277/ 114)
931	SEAL INCLUDING TEMPERATURE RESPONSIVE FEATURE	FOR 113	.Tapered follower or box (277/ 115)
932	.Bi-metallic	FOR 114	..Arcuate (277/116)
933	.Chemical reaction or physical change of state	FOR 115	.Axially related backup member radially actuated by movement of follower (277/116.2)
934	SEAL SWELLS WHEN WET	FOR 116	.Telescoping actuator (277/116.4)
935	SEAL MADE OF A PARTICULAR MATERIAL	FOR 117	..With inserted sleeve expander (277/116.6)
936	.Composite	FOR 118	..Deflected packing (277/116.8)
937	..Glass particles or filament	FOR 119	.Wedging surfaces (277/117)
938	..Carbon or graphite particle or filament	FOR 120	..Internal shell (277/118)
939	.Containing metal	FOR 121	..Split or segmental packing (277/119)
940	..Alloy	FOR 122	...Expanding and contracting (277/120)
941	..Aluminum or copper	FOR 123Elastomeric (277/121)
942	..Silver or gold	FOR 124	...Contracting (277/122)
943	.Ceramic or glass	FOR 125	.Plural packing elements (277/ 123)
944	.Elastomer or plastic	FOR 126	..Nested (277/124)
945	..Containing fluorine	FOR 127	..Diverse (277/125)
946	...PTFE "TEFLON"	FOR 128	EXTERNALLY OPERATED ADJUSTMENT (277/126)
		FOR 129	.Fluid motor (277/127)
		FOR 130	.Circumferential band (277/128)
		FOR 131	.Acting along radius (277/129)
		FOR 132	LATERAL ACCESS TO PACKING BOX (277/130)
		FOR 133	.With distinct closure (277/131)
		FOR 134	..Packing attached (277/132)
		FOR 135	IMPELLER TYPE (277/133)
		FOR 136	.Axially acting (277/134)
		FOR 137	LIQUID BARRIER (277/135)
		FOR 138	WITH ANTIROTATION KEY OR ANCHOR (277/136)
<u>FOREIGN ART COLLECTIONS</u>			
FOR	CLASS-RELATED FOREIGN DOCUMENTS		

- FOR 139 .Radial wall(277/137)
- FOR 140 **WITH DISTINCT RADially ACTING BIAS(277/138)**
- FOR 141 .Unitary packing spacer and bias means (277/139)
- FOR 142 ..U-section (277/140)
- FOR 143 .Common bias for axially spaced packings (277/141)
- FOR 144 .With axially acting bias means (277/142)
- FOR 145 .With axially component (277/143)
- FOR 146 ..Complementary inclined surfaces (277/144)
- FOR 147 ...Transversely symmetrical (277/145)
- FOR 148 .With bias restrainer (277/146)
- FOR 149 .With adjustable loading means (277/147)
- FOR 150 .Individually biased segments (277/148)
- FOR 151 .Circumferentially spaced radially acting springs (277/149)
- FOR 152 ..With radial pin or socket (277/150)
- FOR 153 .Circumferential thrust (277/151)
- FOR 154 .Axial lip or boss (277/152)
- FOR 155 ..Exposed coil spring (277/153)
- FOR 156 .Interfitted segments (277/154)
- FOR 157 .With bridging segments (277/155)
- FOR 158 .Break joint (277/156)
- FOR 159 .Periphery engaging spring (277/157)
- FOR 160 ..Incompatible shapes (277/158)
- FOR 161 ...Radially extending tongues (277/159)
- FOR 162 ...Wave or undulate (277/160)
- FOR 163 ...Polygonal (277/161)
- FOR 164 ..Open-end (277/162)
- FOR 165 ..Spiral (277/163)
- FOR 166 .Embedded or enclosed spring (277/164)
- FOR 167 .Nonmetallic (277/165)
- FOR 168 **ANCHOR EXTENDING THROUGH OR INTERFITTED WITH PACKING (277/166)**
- FOR 169 **HELICAL SEAT (277/167)**
- FOR 170 **SERIALLY ARRANGED, SEPARATELY SEATED OR ANCHORED PACKING MEMBERS (277/167.3)**
- FOR 171 **SINGLE SEAT FORMED BY OPPOSED RECESSES IN PLURAL MEMBERS (277/167.5)**
- FOR 172 **LATITUDINALLY STEPPED OR TAPERED SEAT (277/168)**
- FOR 173 .Arcuate wall (277/169)
- FOR 174 .Oblique wall (277/170)
- FOR 175 ..Plural (277/171)
- FOR 176 ...Parallel (277/172)
- FOR 177 **FLOATING PACKING MEMBER (277/173)**
- FOR 178 .Radially translatable (277/174)
- FOR 179 ..Axially spring pressed (277/175)
- FOR 180 .Additional member (277/176)
- FOR 181 .Elastomeric (277/177)
- FOR 182 **INTERFITTING WITH RADially PROJECTING FLANGE (277/178)**
- FOR 183 **EMBEDDED REENFORCEMENT OPPOSING TAPERED MOUNTED SURFACE (277/179)**
- FOR 184 **WITH COMPRESSION STOP (277/180)**
- FOR 185 **PACKING ATTACHED RETAINER (277/181)**
- FOR 186 .Peripheral shell (277/182)
- FOR 187 ..With radial mounting flange (277/183)
- FOR 188 ..Channel-shaped (277/184)
- FOR 189 .Plural at axially opposed ends (277/185)
- FOR 190 .Resilient (277/186)
- FOR 191 **PACKING CHAMBER OR SEAT WITH SEPARABLE END WALL (277/187)**
- FOR 192 **WITH AXIALLY RELATED BACKING OR RETAINING MEMBER (277/188 R)**
- FOR 193 .With anti-extrusion rings (277/188 A)
- FOR 194 **WITH ANCHOR OR RETAINER (277/189)**
- FOR 195 **COMPOSITE SEAT (277/189.5)**
- FOR 196 **WEDGING PORTIONS (277/190)**
- FOR 197 .Enclosed (277/191)
- FOR 198 **SEGMENTAL (277/192)**
- FOR 199 .Axially related segments (277/193)
- FOR 200 ..L-shaped (277/194)
- FOR 201 ..With radially related segment (277/195)
- FOR 202 ..Coiled or corrugated segment (277/196)
- FOR 203 ..Diametrically opposed splits (277/197)
- FOR 204 .Concentric segments (277/198)
- FOR 205 .Interfitting segments (277/199)
- FOR 206 **AXIALLY SPACED FLANGES WITH CORRUGATED CONNECTING WEB (277/200)**
- FOR 207 **ANNULUS WITH DUCT OR PASSAGEWAY (277/201)**
- FOR 208 .Elongated (277/202)
- FOR 209 **HELICAL (277/203)**

FOR 210 **VOLUTE (277/204)**
FOR 211 **FLEXIBLE U- OR V-CUP (277/205)**
FOR 212 .Radially facing (277/206 R)
FOR 213 ..X-shape (277/206 A)
FOR 214 **RIBBED CONTACT SURFACE (277/207 R)**
FOR 215 .Axially spaced (277/208)
FOR 216 ..Opposite surfaces (277/209)
FOR 217 ...Line contact (277/210)
FOR 218 .Opposite surfaces (277/211)
FOR 219 .Pipe joints or connections (277/207 A)
FOR 220 **FLEXIBLE CUP OR FLANGE TYP(277/212R)**
FOR 221 .Flexible cup type (277/212 C)
FOR 222 .Flange (277/212 F)
FOR 223 .Flexible boot (277/212 FB)
FOR 224 **CORRUGATED CONTACT SURFACE (277/213)**
FOR 225 **CIRCUMFERENTIAL GROOVE IN PERIPHERAL SURFACE (277/214)**
FOR 226 **WITH SPACED POCKETS, GROOVES, OR RECESSES (277/215)**
FOR 227 **SPLIT ANNULUS (227/216)**
FOR 228 .Variable radius (277/217)
FOR 229 .With separate gap or bridging piece (277/218)
FOR 230 ..End secured (277/219)
FOR 231 .With joining structure (277/220)
FOR 232 ..End-to-end tongue and slot (277/221)
FOR 233 ..Beveled or arcuate mating surfaces (277/222)
FOR 234 .With insert (277/223)
FOR 235 ..Hard material (277/224)
FOR 236 **WITH INTERMEDIATE RADIAL PERIPHERAL FLANGE (277/225)**
FOR 237 **FLUENT OR VACUUM CORE (277/226)**
FOR 238 **COMPOSITE (277/227)**
FOR 239 .Elastomeric core (277/228)
FOR 240 .Distinct sheath (277/229)
FOR 241 ..Woven or braided strands (277/230)
FOR 242 .Reentrant contact surface (277/231)
FOR 243 ..Enclosing plural plies (277/232)
FOR 244 .Plural planar or conical plies (277/233)
FOR 245 ..Metal faced (277/234)
FOR 246 .Including metal (277/235 R)
FOR 247 ..Planar coating (277/235 A)
FOR 248 ..Engine gasket (277/235 B)
FOR 249 **METALLIC (277/236)**
FOR 250 **MISCELLANEOUS (277/237 R)**
FOR 251 .Dust guard (277/237 A)

